

Sure - Clamp Access Specifications

- A. General Description: . **Rectangular** Clamping type removable ductwork section with draw latch.
- B. Allowable leakage: 1/2 CFM for 2" W.G.
- C. Provide size as indicated on drawings.
- D. Size : 18" X 18" maximum size
- E. Material : Galvanized ASTM A527
- F. Flange Connection : 18 GA galvanized sheet metal construction.
- G. Seams : Pittsburgh Lock
- H. Access Section : Minimum 26 Gauge galvanized ASTM A527 12" long.
: Fabricated to maintain 100% of ductwork free area.
- I. Clamps : 20 gauge galvanized with zinc coated draw latch. Gasket profile forms to the inside of clamp and seals the outer edges of the ductwork flange.
- J. Gasket : Neoprene gasket 3/16" X 1-1/4"
- K. Seal seams in accordance with SMACNA HVAC Duct Construction Standard - Metal and Flexible.
- L. Install : The removable access section shall not be more than 4" away from the fire damper sleeve break away connection.
- M. Manufacturer :

Langdon Inc.
9865 Wayne Ave Cincinnati, Ohio 45215
Phone (513)733-5955 ext. 223 Fax
(513)733-8050 Attn. : Michael Sandman.
michaelsandman@langdoninc.com

Sure-Clamp Access